

2023 FULL LINE CATALOG

Foodservice



Inspired by great food and great people



Listed by UL, Certified by NSF, NTEP

**HTi-7LH / HTs-7LS / HTm-7LH****HTi-7LH / HTs-7LS / HTm-7LH**
Customer Display**HTi & HTm STANDARD FEATURES**

- Video capability allowing independent videos to play on operator and customer displays simultaneously
- Intuitive and customizable graphical user interface
- Built-in wireless and wired Ethernet standard
- Best seller keys by scale/department
- Search database by description, key word or PLU number
- Swipe between three screens for operator ease of use
- Flashkeys can be laid out by categories or groups
- Product shelf life by days or hours
- Operator, product, and/or recipe notes
- Onscreen operator manual and tutorial videos
- COOL (country of origin labeling) can be created and modified on the scale
- Ability to require operator login
- Label graphics visible in supervisor mode
- Extensive scale backup in supervisor mode
- System can estimate number of additional records that may be added to the scale
- Default values for the four types of products; Fixed Weight, By Count, Random Weight, and Fluid Ounces
- UPC, EAN 13, EAN 128 Barcodes and GS1 DataBar
- Onscreen alphanumeric keyboard and keypad
- Cassette label loading system provides fast and efficient change of label stock
- Meets federal labeling requirements
- Track operator changes
- Remotely access the scale
- **HTm only features:**
 - ValueMax level compensation
 - CodeChecker printhead health agent
 - On-Demand processor
 - AC wireless capability

HTs STANDARD FEATURES

- Video playback on operator display
- Intuitive and customizable graphical user interface
- Best seller keys by scale/department
- Search database by description, key word or PLU number
- Swipe between screens for operator ease of use
- Flashkeys can be laid out by categories or groups
- Product shelf life by days or hours
- Operator, product, and/or recipe notes
- Onscreen operator manual and tutorial videos
- COOL (country of origin labeling) can be created and modified on the scale
- Ability to require operator login
- Label graphics visible in supervisor mode
- Extensive scale backup in supervisor mode
- System can estimate number of additional records that may be added to the scale
- Default values for the four types of products; Fixed Weight, By Count, Random Weight, and Fluid Ounces
- UPC, EAN 13, EAN 128 Barcodes and GS1 DataBar
- Onscreen alphanumeric keyboard and keypad
- Cassette label loading system provides fast and efficient change of label stock
- Meets federal labeling requirements
- Track operator changes
- Remotely access the scale

HT SCALE COMPARISON

Model	HTs	HTi	HTm
Performance	Standard	Premium	Platinum
Processor	IMX6 Solo	IMX6 Dual	IMX6 Dual - On Demand
Operating System	Embedded Linux	Embedded Linux	Embedded Linux
RAM (Standard) Minimum	1 GB DDR3 RAM	1 GB DDR3 RAM	2 GB DDR3 RAM
Program/Data Storage	8 GB	16 GB	32 GB
Operator Display Size(s)	10.1" wide TFT LCD, (1024x600) LED backlight, 5 Wire Touch		
Customer Display Size(s)	7" wide TFT LCD Elevated 7" wide TFT LCD"	7" wide TFT LCD Elevated 7" wide TFT LCD Elevated 10" wide TFT LCD"	7" wide TFT LCD Elevated 7" wide TFT LCD Elevated 10" wide TFT LCD"
ValueMax Auto-Leveling Compensation	No	No	Yes
Label Loading	Cassette Style	Cassette Style	Cassette Style
Printer	2.25" wide label stock 8 dot/mm printhead 5 ips Print Speed	2.25" wide label stock 8 dot/mm printhead 5 ips Print Speed	2.25" wide label stock 8 dot/mm printhead 5 ips Print Speed"
USB Ports	(2)Ext, USB 2.0		
External Printer Options	No	Yes	Yes
Scanner	N/A	Image Scanner	Image Scanner
Internet Browser	Optional	Standard	Standard
Video	Yes, HD resolution on Operator side only	Yes, HD, simultaneous operator and customer videos	
Audio	Headphone mini Jack	Dual Stereo Speakers (Internal), Headphone mini Jack	
Scale Alerts	Yes, message alerts, network connectivity, printer, and planogram updates		
Graphical User Interface (GUI)	Intelligent, industry leading GUI with swipe control		
# of Swipable Screens (GUI)	2	3	3
Flexible Screen Layouts	Yes, standard screen layouts with customization		
Wireless	Ethernet wired (Standard), wireless 802.11 a/b/g/n (Optional)	Wired and wireless 802.11 a/b/g/n (Standard)	Wired and wireless 802.11 a/b/g/n/ac (Standard)
Hands-Free Login	N/A	Optional	Optional
PDF Viewer	Optional	Optional	Standard
Auto Cutter & Linerless Label Capability	No	Optional	Optional
CodeChecker Printhead Health Agent	No	No	Yes

Listed by UL, Certified by NTEP

STANDARD FEATURES

- Large elevated 14" touch screen display
- Intuitive and customizable graphical user interface
- Built-in wireless and wired Ethernet standard
- Best seller keys
- Search by image, description or PLU number
- COOL (country of origin labeling)
- UPC, EAN 13, EAN 128 Barcodes and GS1 DataBar
- Onscreen keypad
- Cassette label loading system provides fast and efficient change of label stock
- Meets federal labeling requirements
- Remotely access the scale using Hobart specific software
- Goes back to home page when not used for 30 seconds
- Onscreen prompts for ease of use
- Optional barcode scanner



Certified by NSF



PS40

STANDARD FEATURES

- Simple touch key operation
- Bright operator and customer backlit displays
- Audible beep response
- 6V 4-amp rechargeable battery comes standard
- Power cord comes standard
- Up to 50 programmable speed keys
- 30 lb. x .01 weighing
- Weight/price/total price displayed to 6 digits
- Small footprint – 13.9"W x 13"L x 4.9"H
- NSF Certified and legal for trade

MECHANICAL SCALES PR30 AND PR309

Certified by NSF



PR30

PR309

STANDARD FEATURES

- Full temperature compensating mechanism for stability in environment changes
- Double face dials for readability from both sides of scale
- Two automatic dampeners reducing indicator oscillations for quick reading
- Easy to clean chrome finished housing
- Durable stainless steel pan for easy unloading and cleaning
- **PR30** meets or exceeds weights and measures H-44, Class III requirements
- **PR309** meets weights and measures H-44, Class IV requirements

MECHANICAL SCALE HBR302-1

Listed by UL, Certified by NTEP

STANDARD FEATURES

- Easy-to-read display
- Legal for trade
- Rechargeable battery or AC adaptor
- Energy saver setting – set shutoff time to extend battery life
- Low battery indicator
- Check weighing with over/under blue LED indicator
- Batch weighing
- Tilt and rotatable display for easy viewing
- Toggle between (lb./kg.)
- Stainless steel
- Tare indicator
- One touch and reset tare
- Stable weight indicator
- Net/gross weighing
- Automatic zero tracking
- Leveling leg set
- Leveling indicator



HBR302-1